

IN THE UNITED STATES
PATENT AND TRADEMARK OFFICE

PATENT APPLICATION

5

LENSLESS OPTICAL SERVO SYSTEM
FOR AN OPTICALLY ASSISTED DISK DRIVE

BACKGROUND OF THE INVENTION

10

1. Field of the Invention

The invention broadly relates to optical servo systems. More particularly, the invention relates to the optical detection system used in an optically assisted disk drive to detect marks on a magnetic disk and thereby precisely locate the magnetic read/write head relative to tracks on the magneto-optical disk.

15

2. Brief Description Of The Prior Art

20

Since the introduction of the personal computer in the 1970s and the development of the floppy disk, the need for greater and greater amounts of storage space has continued unabated. The original floppy disk could store less than 100 kilobytes and the most commonly used (3.5 inch) floppy disk today, introduced in the late 1980s can store 1.4 megabytes. Although fixed (hard) disks now store many gigabytes, there remains a need for removable storage media with high capacity.

25

002790-0267650

High capacity removable storage media became popular in the 1980s with the advent of desktop publishing (DTP). Relatively large, clumsy, and undependable

5 "cartridges" from Syquest, Iomega, and other companies were used to transport large DTP files that could not fit on a floppy disk, to a printing plant. High capacity storage media is still in demand today for transporting large files when a broadband connection is not available and for
10 transporting confidential information without using the public network.

One high capacity removable media system which is growing in popularity is the "a:drive" from OR Technology
15 Inc. of Campbell, Calif. While its outward appearance is almost indistinguishable from that of a 3.5 inch, 1.44 megabyte floppy disk drive, the "a:drive" provides 120 megabytes of storage on ultra high density disks, known as "LS-120" or "Superdisk" media. At the same time, the
20 "a:drive" product is compatible with current and legacy 3.5 inch technology and can read and write to both 720 kilobyte and 1.44 megabyte disks. As its name implies, the "a:drive" can serve as a bootable drive in any system in which it is installed.

25

FIG. 2 shows in more detail how a split beam arrangement is used to detect either the reflection profile for a linear encoder when reading/writing 3.5 disks or the markings on the surface of an LS-120 disk when reading/writing it. The sensor system carried on the arm 22 includes, in addition to the light detector 30, a laser source 32, a hologram 34, a lens array 36 and a rooftop mirror 38. Light from the laser source 32 is diffracted by the hologram 34 and focused by the lens array 36. The rooftop mirror directs the light and reflections to either the linear encoder 24 or the surface of an LS-120 disk 40.

It can be appreciated from prior art FIG. 2 that the sensor system requires multiple passive optical elements, all of which must be aligned during the assembly process. The alignment requires expensive tooling. Each passive element occupies a finite space and additional space must be provided for the alignment tooling. The sizes of the elements also require a large mechanical supporting structure.

In addition, it will be appreciated by those skilled in servo system shown in prior art FIG. 2 is relatively large and will require a "full height" drive bay to be accommodated.

Additionally those skilled in the art will recognize th
servo system for an LS-120 type disk drive requires a quadrature
between the adjacent sensors; that the detection of the sensors m
synchronous; and that the first stage of the pre-amplifier
5 used in a typical optical servo system would be more
effective by amplifying the tangential and radial tracking
signals only and not the DC component, thereby allowing for
a larger gain and more signal amplitude.

10 *Sub A17* Co-owned co-pending application Serial Number
097-----discloses one solution to the problems of the
prior art devices. In both the prior art and the co-owned
co-pending application, light from a laser source is focused
by passive optical elements to form three highly focused
15 points of light at the plane of the disk. Other passive
optical elements gather reflected light from these three
points and focus the reflected light onto three separate
detectors. The detectors produce track sensing signals that
include a low noise pair of sinusoidal signals in exact
20 quadrature indicating the track radial position.

SUMMARY OF THE INVENTION

It is therefore an object of the invention to provide an improved positioning device (referred to
5 hereinafter generically as optical servo systems) that can be used for metrology, optical data storage, or data storage systems that use optical features on the media for tracking purposes.

10 It is also an object of the invention to provide optical servo systems for data storage devices that do not require alignment of elements during assembly of the data storage devices.

15 It is another object of the invention to provide an optical servo system for a data storage device that reduces the overall cost of the data storage device.

20 It is still another object of the invention to provide an optical servo system for a data storage device that is smaller in size than conventional optical pickup systems.

25 It is also an object of the invention to provide an optical servo system that provides built-in quadrature phase shift.

photodetectors. The convolution of this light pattern and a mating geometric pattern on the photodetectors causes the photodetectors to generate signals representing the position of the track on the disk.

5

According to a presently preferred embodiment of the invention, set forth herein to illustrate the principals of the invention, a laser diode and three detectors are formed on the same silicon substrate. Further, according to this illustrative preferred embodiment, sinusoidal metalization (a form of aperture) is applied to the detectors in the radial direction (radial relative to the LS-120 disk); the period of the sinusoidal metalization is approximately two times the tracking pitch of the disk; the metalization on the first detector is offset radially approximately ninety degrees behind the metalization on the second detector; and the metalization on the third detector is offset radially approximately ninety degrees ahead of the metalization on the second detector. Alternatively, in lieu of sinusoidal metalization an absorbing sinusoidal feature may be provided.

Preferably, each detector is provided with two sinusoidal patterns, approximately one hundred eighty degrees out of phase with each other with respect to the tangential direction (tangential relative to the LS-120 disk). The patterns are subtracted to remove the DC

component (noise) of the tracking signal. This allows for a differential detection system to occur before the tangential modulation of the tracking signal is removed. Thus, the first stage of a pre-amplifier is more effective by
5 amplifying the tangential and radial tracking signals only and not the DC component, thereby allowing for a larger gain and more signal amplitude.

The silicon substrate is also provided with a
10 source laser diode that is aligned so the reflection from the disk is substantially centered on the second detector. A fold mirror is also provided to direct light from the source laser diode to the disc in a manner well known by those skilled in the art.

15 The invention features an positioning systems, (such as optical servo systems), which perform optical sensor functions without the need for an imaging optic, utilizing only unfocused laser light and patterned
20 photodetectors.

Advantages of the invention include (1) obviation of separate holographic optical elements required by the prior art (as well as other lens elements) to reduce system
25 cost; (2) a less complex assembly process for the devices contemplated by the invention is achieved by (a) eliminating the need to align and attach any optical elements to the

002190 061500

laser detector module, (b) eliminating the need to steer
light onto a detector during the assembly process since all
reflected light from the media will have all the tracking
information required to operate the system, and (c) since
5 the radial shift required to make the tracking signals in
quadrature is built into the aperture, there is no alignment
requirement for this parameter; and (3) end users experience
a lesser degree of complexity and cost in installing the
device contemplated by the invention in their products since
10 there is less material physically present at the top of the
detector system which nominally requires delicate handling.

Additional objects and advantages of the invention
will become apparent to those skilled in the art upon
15 reference to the detailed description taken in conjunction
with the provided figures.

BRIEF DESCRIPTION OF THE DRAWINGS

20 FIG. 1 is a simplified schematic diagram of a
prior art LS-120 type disk drive;

FIG. 2 is a simplified schematic diagram of a
prior art optical pickup system for an LS-120 type disk
25 drive;

FIG. 3 is a simplified schematic diagram illustrating the principles of the invention;

FIG. 4 is a simplified schematic diagram of a presently preferred embodiment of the invention; and

FIG. 5 is an enlarged detail of a portion of FIG. 4.

10

DETAILED DESCRIPTION

Turning now to FIG. 3, a lensless optical servo system 100 has an unfocused, unmasked, undiffracted light source 102 and three patterned photodetectors 104, 106, 108. The unfocused, unmasked, undiffracted light is reflected by the markings on an LS-120 disk 40 and the reflected light carries the pattern of the markings the considerable distance in its far-field to the photodetectors 104, 106, 108. The convolution of this light pattern and a mating geometric pattern 110, 112, 114 on the photodetectors causes the photodetectors to generate signals representing the position of the track on the disk.

More particularly, the pattern on each photodetector filters the reflected light so that only the radial and tangential tracking information is seen by the detectors. Preferably, the source 102 is aligned so that

the reflected light is substantially uniformly distributed about the center detector 106.

Turning now to FIGS. 4 and 5, according to a presently preferred embodiment, a laser diode 102 and three 104, 106, 108 detectors are formed on the same silicon substrate 101. The laser diode 102 is angled toward the detectors by an angle α and a fold mirror 103 mounted adjacent to the output of the laser diode 102 deflects the beam from the diode toward an LS-120 disk (not shown). As seen best in FIG. 5, sinusoidal metalization 110, 112, 114 is applied to the detectors 104, 106, 108 in the radial direction (radial relative to the LS-120 disk).

The period of the sinusoidal metalizations is, according to a preferred embodiment of the invention, approximately two times the tracking pitch of the disk. The sinusoidal metalization 110 on the first detector 104 is offset radially approximately ninety degrees behind the sinusoidal metalization 112 on the second detector 106; and the sinusoidal metalization 114 on the third detector 108 is offset radially approximately ninety degrees ahead of the sinusoidal metalization 112 on the second detector 106.

Preferably, each detector 104, 106, 108 is provided with two sinusoidal patterns 110a, 110b, 112a, 112b, 114a, 114b. Pattern 110a is approximately one hundred eighty

degrees out of phase with, and spaced apart in the tangential direction (tangential relative to the LS-120 disk) from pattern 110b. Similarly, pattern 112a is approximately one hundred eighty degrees out of phase with, and spaced apart in the tangential direction from pattern 112b; and pattern 114a is approximately one hundred eighty degrees out of phase with, and spaced apart in the tangential direction from pattern 114b. The patterns are preferably applied lithographically.

10

The signals filtered by the patterns are subtracted to remove the DC component of the tracking signal. This allows for a differential detection system to occur before the tangential modulation of the tracking signal is removed. Thus, the first stage of a pre-amplifier is more effective by amplifying the tangential and radial tracking signals only and not the DC component, thereby allowing for a larger gain and more signal to noise ratio.

15

20

The lensless optical servo system of the invention is smaller and less expensive than the prior art systems, yet it meets or exceeds the servo signal requirements of an LS-120 disk drive. The lensless optical servo system of the invention does not require the costly alignment step optical systems require when assembling an LS-120 disk drive.

25

There have been described and illustrated herein
embodiments of a lensless optical servo system. While
particular embodiments of the invention have been described,
it is not intended that the invention be limited thereto, as
5 it is intended that the invention be as broad in scope as
the art will allow and that the specification be read
likewise.

Thus, while a particular number of detectors have
10 been disclosed, it will be appreciated that other numbers
(at least two) could be utilized. Further, while the
invention is described in the context of a preferred
embodiment where the phase shift from detector to detector
is approximately ninety degrees, this is not intended to be
15 a characteristic that limits the scope of the invention.
For example, those skilled in the art will appreciate that
an approximately (plus or minus) one hundred twenty degree
phase shift between detectors would be suitable for
practicing the invention. In this scenario, if three
20 detectors were used, the one hundred twenty degree patterns
used on the first and third detectors would be offset from
each other by one hundred twenty degrees.

It should also be recognized that although the
25 invention has been described with reference to and for use
with an LS-120 disk drive, it may be used in other types of
optical and magnetic drives. Moreover, it may be used in

other positioning devices. It will therefore be appreciated by those skilled in the art that yet other modifications could be made to the provided invention without deviating from its spirit and scope as so claimed.